

# Aqua Mix® High-Gloss Sealer

## 1 Product Name

Aqua Mix® High-Gloss Sealer

## 2 Manufacturer

Custom Building Products  
 Technical Services  
 10400 Pioneer Boulevard, Unit 3  
 Santa Fe Springs, CA 90670  
 Customer Support: 800-272-8786  
 Technical Services: 800-282-8786  
 Fax: 800- 200-7765  
 Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)

## 3 Product Description

A specially formulated water-based sealer of acrylic polymers that provides both a stain-resistant surface seal and a durable high-sheen finish, eliminating the need for two products. May also be used as a pre-grouting sealer. Allows moisture vapor transmission and is unaffected by ultra-violet light.

### Key Features

- One step sealer & finish
- Excellent stain protection
- High-gloss finish

### Uses

- For clay pavers including Saltillo, terra-cotta and adobe, cement tile, quarry, slate and sandstone.
- For interior applications only.

### Benefits of Product in the Installation

- Excellent stain resistance to household contaminants (CTI-072)
- Excellent mar resistance
- High-gloss sheen

### Limitations to the Product

- Not recommended for use on smooth glazed ceramic or porcelain tile, as surface must be rough-textured to ensure adequate bonding.
- Do not allow product to come in contact with any non-recommended surface.
- Not recommended for use in or around pools, showers or areas subject to standing water.
- Not recommended for use on countertops.
- Keep surface clean and dry to reduce possibility of slip-fall accidents.

## 4 Technical Data

### Environmental Consideration

Complies with all Federal EPA and SCAQMD standards for VOC

## 5 Instructions

### General Surface Prep

**USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.**



Surface should be dry, clean and free of waxes, sealers, or finishes. Do not apply directly over silicone sealers, oil or wax based finishes. **Aqua Mix® Sealer & Coating Remover will strip the surface and remove wax or old acrylic finishes.** Place a few drops of water on various tiles. If water doesn't penetrate, additional removal is necessary. New installations need to be dry at least 48 hours before application. Clay and Saltillo tile may require extended drying time depending on temperature and humidity. Make sure the tiles are completely dry before application. Test product in an inconspicuous area to ensure desirable results.

Exterior applications must meet moisture conditions - [read CUSTOM Technical Bulletin 49](#) for details.

### Application of Product

Read entire label before using. For new installations sealer can be applied as soon as 48 hours after grouting. Surface must be clean, dry and free of existing sealers and coatings. Apply 2-3 coats of sealer with a clean dense sponge, brush or paint pad applicator in thin, even coats. Allow 30 minutes drying time between coats. Avoid puddling.

### Pre-Grouting Application

Apply over clean stone or tile a minimum of 2 hours prior to grouting - follow application procedures above.

### Drying Time

Ready for surface traffic 6 hours after final coat. Keep area dry for at least 12 hours. Achieves a full cure in 24 hours.

### Cleaning of equipment

Clean tools with soap and water immediately after use.

### Storage

- Close container tightly after each use
- Store in original container only
- Store and use between temperatures of 45°F to 85°F (7°C to 29°C)
- Dispose of residue or any unused leftover product in accordance with applicable federal, state, and local requirements



# CUSTOM®

# Aqua Mix® High-Gloss Sealer

## Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains glycol ether monobutyl ether. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting and seek medical attention. DO NOT SPRAY.

## 6 Availability & Cost

Location	Item Code	Size	Package
USA	100726-4	1 qt (946 ml)	Bottle
USA	100727	1 gallon (3.8 L)	Bottle
Canada	C100726-4	1 qt (946 ml)	Bottle
Canada	C100727	1 gallon (3.8 L)	Bottle

## 7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at [www.custombuildingproducts.com/product-warranty](http://www.custombuildingproducts.com/product-warranty) or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

## 8 Product Maintenance

Do not use cleaners containing ammonia, acids or bleach. Use an appropriate TileLab® or Aqua Mix® neutral cleaner. Tile industry experts recommend periodic testing of sealed surfaces. Apply a few drops of water on the surface. If it soaks in, an additional application will be necessary to maintain peak performance.

## 9 Technical Services Information

For technical assistance, contact Custom technical services at 800-282-8786 or visit [custombuildingproducts.com](http://custombuildingproducts.com).

## 10 Filing System

Additional product information is available from the manufacturer upon request.

### VOC Content

Maximum VOCs: 51 grams per liter

### Expected Wear

- Will vary depending on hardness and texture of surface, type of area, surface wear, frequency and type of maintenance products used
- Weather conditions, harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners will affect wear
- Expected wear of all sealers is dependent on many environmental issues and intended use. Review our technical bulletin, TB84, at our website for more information.

### Related Products

Aqua Mix® Concentrated Stone & Tile Cleaner



# Aqua Mix® High-Gloss Sealer

---

## Coverage

Depends on type of stone or tile, porosity and texture of surface, temperature, humidity, and method of application.

Size	Min Coverage	Max Coverage
1 Gallon (3.78 L)	300 ft <sup>2</sup> (28 M <sup>2</sup> )	1000 ft <sup>2</sup> (92.9 M <sup>2</sup> )

