

Grout Release

Release for all Cement, Epoxy, Urethane Grouts and Mortars for use with:

- | | | |
|---------------|----------------|------------------|
| ■ Quarry Tile | ■ Ceramic Tile | ■ Porcelain Tile |
| ■ Glazed Tile | ■ Marble | ■ Granite |
| ■ Travertine | ■ Slate | ■ Grout |
| ■ Quartz | ■ Brick | ■ Terrazzo |

Uses

- | | | |
|-----------------------|-----------|--------------|
| ■ Interior & Exterior | ■ Kitchen | ■ Showers |
| ■ Restrooms | ■ Patios | ■ Drive Ways |

Special Features

- | | | |
|-------------------------|---------------------|------------------|
| ■ Easy-to-Use | ■ Weather Resistant | ■ Low Toxicity |
| ■ Stain Resistant | ■ Water Resistant | ■ Non Coating |
| ■ Acid Resistant | ■ Non Yellowing | ■ Salt Resistant |
| ■ Freeze/Thaw Resistant | ■ U.V. Transparent | ■ Slip Resistant |

PRODUCT DESCRIPTION

KEEP OUT OF REACH OF CHILDREN. This product is formulated for sealing surfaces prior to grouting the surface. **Grout Release** provides resistance against cement, epoxy, urethane and new age grouts from “sticking” to the surface and potentially staining the surface. **Grout Release** is a unique polymerized silicone formulation designed to repel all types of grout and mortar residue. **Grout Release** penetrates into the surface and forms an invisible barrier that is resistant to grout and mortar sticking to the surface and potentially staining the surface, while allowing vapor to escape. **Grout Release** is not a surface coating and will not alter the natural look. **Grout Release** can be used on interior and exterior applications. **Grout Release** is U.V. transparent and will not yellow under any circumstances.

Sample Testing

Due to the differences of each substrate, several inconspicuous test patches should be completed to assure maximum performance. User must determine suitability of the product for their intended use.

NEW INSTALLATIONS - APPLICATION INSTRUCTIONS

Read entire label and SDS before using. **Grout Release** should not be diluted or thinned in any way. **Grout Release** should be used as is direct from approved container.

Before Grouting: Apply **Grout Release** to the surface prior to grouting. This step will allow quick and easy cleanup after grouting. Grout can stain many surfaces if this procedure is not used prior to the grouting process. Apply **Grout Release** using a Mira Brush, Micro Fiber or a clean towel. Apply enough to wet the surface. (See coverage charts) **Be careful not to saturate the open grout joints.** Allow **Grout Release** to stand for approximately 3 - 5 minutes for maximum penetration. All excess must be removed at this time by buffing surface with a clean dry towel or Micro-Fiber cloth. This is very important on polished, glazed and porcelain surfaces. Allow **Grout Release** to cure for 6 - 12 hours before continuing with the grouting procedure.

Residue Remover

To remove accumulated **Grout Release** residue, use Miracle Residue Remover as directed.

Cure Time

Grout Release will be dry to the touch in 1 - 3 hours and may be used for normal foot traffic. **Grout Release** must sit for 6-12 hours before grouting.

For optimum results the area should be kept dry and free from staining materials for 72 hours.

MAINTENANCE

For ongoing maintenance instructions please refer to Miracle Sealants Care Guide. Refer to the Miracle Sealants Product Recommendation Chart for specific product recommendations.

Storage

Store **Grout Release** in the original container, properly sealed to avoid contamination and solvent evaporation. Stored at 77 °F (25 °C), **Grout Release** will have a shelf life of 12 months.

Technical Support

For additional technical support, contact Miracle Sealants Company at 1-800-350-1901

Office Hours

Monday - Friday from 8:30 am - 5:00 pm PT.
1-800-350-1901 • Fax: 1-626-443-1435 website:
www.miraclesealants.com

Product Damaged During Transportation

If product is damaged during transportation contact Info Trac @ 1-800-535-5053

Additional Product

Miracle Sealants Company offers a complete line of water & stain repellents, sealers, cleaners, polishing compounds, diamond abrasives, machinery and accessories for the tile, stone, concrete, metal, fabric and carpet professional or do-it-yourself specialist.

WARRANTY & CAUTIONS

Warranty

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealants Company shall be to replace such products proven to be defective. Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein. Neither seller nor manufacturer shall be liable for any injury or inability to use this product.

Caution

Grout Release contains combustible petroleum distillates. All solvents must be considered toxic and must be used in a well ventilated area. Good ventilation means that fresh air is flowing in such a way as to feel a slight breeze. Open windows and use fans to circulate air. Continue to ventilate until vapors are eliminated. Exposure to high vapor concentration must be avoided. Inhaling the vapors can be harmful. Keep away from heat and open flames. Avoid prolonged contact with skin. Chemical resistant gloves should be worn at all times. Keep small children and pets out of the area until product or surface has thoroughly dried. Refer to the SDS for additional information.