

Tile Brite

To Polish and Restore

- Mosaic Tile
- Porcelain Tile
- Ceramic Tile
- Quarry Tile

Uses

- Floors
- Restrooms
- Showers
- Kitchens

Special Features

- Easy-to-Use
- Fast
- Effective
- Non-Coating
- Never Yellows
- No Stripping
- Cost Effective
- Finish Last Up to 5 Years

PRODUCT DESCRIPTION

KEEP OUT OF REACH OF CHILDREN. **Tile Brite** is a unique, natural, non-wax powder compound for polishing and restoration of most ceramic, quarry, mosaic and porcelain tiles. **Tile Brite** requires no special training to use. When used properly, **Tile Brite** will give a long lasting luster, while providing a durable slip resistant surface. **Tile Brite** will not yellow. Use of **Tile Brite** with appropriate **511 Impregnator** and **Porcelain & Ceramic Tile Cleaner** offers the most complete program available for the ongoing care and protection of ceramic tile. **Tile Brite** eliminates the need for stripping and waxing of tile.

Tile Brite is available in black, gray and white for the right grout color.

Sample Testing

Due to the differences of each material, several inconspicuous test patches should be completed to assure maximum performance. **User must determine suitability of the product for their intended use.**

Protect Neighboring Surfaces

Always protect neighboring surfaces including wood, metal, carpet, baseboards, fabric, landscaping, etc.

APPLICATION INSTRUCTIONS

Read the entire label and SDS/PDS before starting.

- a. All previous applied sealers, coatings and/or waxes must be removed using **Mira Strip** or **Finish Sealer Stripper** as directed.
- b. If the grout is very dirty scrub using **HDAC** as directed.
- c. If the floor is very dirty or old (typically 5 years or more), use **Tile Restor** first as directed for optimum results.
- d. Apply a small amount of water to the tile and grout surface. Work in approximately 25 - 35 square feet at a time. Do not work large areas.
- e. Sprinkle a handful of **Tile Brite** onto the wet surface (approximately 5 ounces per 25 square feet of tile).
- f. Buff the **Tile Brite** creating a slurry with natural hair brush or pad. (A **Marble Master** or similar floor machine is preferred). Approximately 20 minutes per 25 - 35 square feet of tile.
- g. Move slurry aside with a squeegee. Check for desired luster. Work longer for additional luster. When the desired luster is achieved, squeegee the **Tile Brite** slurry to the next section and add **Tile Brite** and water as needed. **DO NOT ALLOW Tile Brite DRY ON THE SURFACE.**
- h. Remove excess slurry with a wet vacuum. Wet the surface with clean water and buff with the same brush pad. This procedure will remove any residue. **DO NOT ADD MORE Tile Brite.**
- i. Rinse the surface with **Tile & Stone Cleaner** and let area dry completely.

Heavy Duty Cleaning: Use **Phosphoric Acid Cleaner**, **HDAC** or **Liquid Poutlice** as directed.

Light Cleaning: Use **Porcelain & Ceramic Tile Cleaner**, **Tile & Stone Cleaner**, **Grout Cleaner** or **Counter Kleen** as directed.

Water, Stain & Slip Protection

To protect cleaned area from future soiling and staining and increase static coefficient of friction, we recommend applying the appropriate **Miracle Penetrating Sealer/Impregnator**.

Coverage

Coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface and application methods. Used as directed, **Tile Brite** will cover approximately 80 - 115 square feet per pound (7 - 11 square meters).

MAINTENANCE

The **Tile Brite** finish will last approximately 3 - 5 years. Use **Porcelain & Ceramic Tile Cleaner** as directed for ongoing cleaning. For ongoing maintenance instructions please refer to **Miracle Sealants Care Guide**. Refer to the **Miracle Sealants Product Recommendation Chart** for specific product recommendations.

Future Restoration

Use **Tile Brite** as directed.

Storage

Store **Tile Brite** in the original upright container, properly sealed and unmixed. Stored at 77° F (25° C), **Tile Brite** will have a shelf life of 12 months. Do not allow to freeze.

Technical Support

For additional technical support, contact Miracle Sealants Company at 1-800-350-1901

Office Hours

Monday - Friday from 8:30 am - 5:00 pm PT.
1-800-350-1901 • Fax: 1-626-443-1435 website:
www.miraclesealants.com

Product Damaged During Transportation

If product is damaged during transportation contact Info Trac @ 1-800-535-5053 for additional information 24 hours a day.

Additional Products

Miracle Sealants Company offers a complete line of water & stain repellents, sealers, cleaner, polishing compounds, diamond abrasives, machinery and accessories for the tile, stone, concrete, metal, fabric and carpet professional or do-it yourself specialist.

Caution

Use in a well ventilated area. This product contains a corrosive and must be used as directed. **KEEP OUT OF REACH OF CHILDREN.** Avoid contact with food or beverages and risk of accidental ingestion. Do not transfer to other bottles or containers. Protect skin and eyes. If exposed flush with water. Chemical resistant gloves should be worn at all times. Keep small children and pets out of the area until product or surface has thoroughly dried. **Refer to MSDS for additional information.**

Warranty

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealants Company shall be to replace such products proven to be defective. **Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein.** Neither seller nor manufacturer shall be liable for any injury or inability to use this product.