

Tile, Stone & Grout Sealer

Water Base

Water & Stain Protection For

- | | | | |
|-----------------|---------------|------------------|---------------|
| ■ Grout | ■ Quarry Tile | ■ Ceramic Tile | ■ Glazed Tile |
| ■ Granite | ■ Marble | ■ Limestone | ■ Terrazzo |
| ■ Saltillo Tile | ■ Slate | ■ Flagstone | ■ Concrete |
| ■ Brick | ■ Travertine | ■ Porcelain Tile | |

Uses

- | | | | |
|-------------|-------------|-----------|--------------|
| ■ Kitchens | ■ Bathrooms | ■ Showers | ■ Health |
| ■ Driveways | ■ Patios | ■ Garages | ■ Facilities |

Special Features

- Easy-to-Use
- Interior & Exterior Use
- Oil Resistant
- Retains Natural Color
- Odorless
- Non Flammable

NO PERFLUOROCTANE SULFONATE (PFOS); NO PERFLUOROCTANOIC ACID (PFOA)

PRODUCT DESCRIPTION

KEEP OUT OF REACH OF CHILDREN. **Tile, Stone & Grout Sealer** is a unique water base formulation designed for the protection of all surfaces where a water base product is required. **Tile, Stone & Grout Sealer** penetrates into the surface and forms an invisible barrier that is resistant to moisture and stains, while allowing vapor to escape. **Tile, Stone & Grout Sealer** is not a surface coating and will not alter the natural look. **Tile, Stone & Grout Sealer** can be used on interior and exterior applications. **NO (PFOS) or (PFOA)**

Test Data

Independent laboratory tests show **Tile, Stone & Grout Sealer** out performs competitive products. Test results are available upon request for staining.

NOTE: For any questions concerning grout-refer to the grout manufacturers specifications. **Tile, Stone & Grout Sealer** will not stop acid etching.

Slip Resistance

Tile, Stone & Grout Sealer increases the static coefficient of friction on all surfaces. **Tile, Stone & Grout Sealer** has been used successfully for compliance with the American Disability Act's recommendations for slip resistance (ASTM C 1028-89) on polished & honed surfaces.

Sample Testing

Due to the differences of each material, several inconspicuous test patches should be completed to assure maximum performance. **User must determine suitability of the product for their intended use.**

Protect Neighboring Surfaces

Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non masonry surfaces.

NEW INSTALLATIONS - APPLICATION INSTRUCTIONS

Read entire label and SDS/PDS before using. This product should be used directly from container and is not under any circumstances to be thinned or diluted with anything before use. Sealing As a Grout Release

Apply **Tile, Stone & Grout Sealer** to all surfaces prior to grouting. This step will allow quick and easy cleanup after grouting. Grout can stain many surfaces if this procedure is not used prior to the grouting process. Apply **Tile, Stone & Grout Sealer** using a **Mira Brush** or a clean towel. Apply enough to wet the surface. Be careful not to saturate the open grout joints. Allow **Tile, Stone & Grout Sealer** to stand for approximately 3 - 5 minutes for maximum penetration. All excess must be removed at this time by buffing surface with a clean dry towel. This is very important on polished, glazed surfaces, and porcelain surfaces. Allow **Tile, Stone & Grout Sealer** to cure for 6 - 12 hours before continuing with the grouting procedure.

After Grouting: Once grouted, make sure that all grout residue is removed from the surface with a clean sponge and water. Allow grout to dry at least 24 - 72 hours. If grout clean up is not performed effectively, an additional cleaning may be necessary to remove remaining grout residue or haze. For this procedure use **Phosphoric Acid Cleaner**, **HDAC (Heavy Duty Acidic Cleaner)** or **Epoxy Grout Film Remover** as directed.

Grout Sealing

Once the area has completely dried, proceed with the sealing of the grout for water and stain resistance. Apply **Tile, Stone & Grout Sealer** to all grout with a thin paintbrush. Any excess sealer that gets on the surface should be wiped off with a clean towel before it dries. On larger jobs, grout can be sealed by retreating the entire area including the tile or stone surface a second time. Be careful not to allow sealer to puddle or dry on presealed surfaces.

Existing Installations - Surface Preparations

Surface must be dry and free of contaminants, including previously applied sealers, dirt, lime & hard water deposits, efflorescence, rust & other heavy dirt and grime.

Floor Coating/Wax Removal: To remove existing coatings and/or waxes, use **Mira Strip** or **Finish Sealer Stripper** per the instructions.

Heavy Duty Cleaning: To remove lime and hard water deposits, efflorescence, rust, grease and other heavy dirt and grime use **HDAC (Heavy Duty Acidic Cleaner)** or, **Phosphoric Acid Cleaner** as directed. For a non-acid deep clean use **Liquid Poultice** as directed.

Light Duty Cleaning: Use **Tile & Stone Cleaner**, **Porcelain & Ceramic Tile Cleaner**, **Counter Kleen**, or **Limestone/Travertine Soap** as directed.

Color & Gloss Enhancement

For color and gloss enhancement, use **511 Seal & Enhance**, **Mira Matte** or **High-Gloss Finish Sealer** as directed.

Existing Installations - Application Instructions:

Follow the application instructions previously mentioned, except now, seal the grout and tile or stone surface at the same time. When treating surfaces together, make sure that the recessed grout is saturated with sealer.

Cure Time

Tile, Stone & Grout Sealer will be dry to the touch in 1 - 3 hours and may be put into service. For optimum results the area should be kept dry and free from staining materials for 24 - 72 hours.

Coverage

Coverage will vary depending on the density, porosity, texture, surface absorption, weather, time solution left on surface and application methods. Used as directed, **Tile, Stone & Grout Sealer** will cover between 500 - 1,500 sq.ft. per gallon (45 - 135 square meters per 3.785 liters).

MAINTENANCE

For ongoing maintenance instructions please refer to **Miracle Sealants Care Guide**. Refer to the **Miracle Sealants Product Recommendation Chart** for specific product recommendations.

Storage

Store **Tile, Stone & Grout Sealer** in the original container, properly sealed to avoid contamination and evaporation. Stored at 77° F (25° C), **Tile, Stone & Grout Sealer** will have a shelf life of 12 months. Do not allow to freeze.

Technical Support

For additional technical support, contact Miracle Sealants Company at 1-800-350-1901

Office Hours

Monday - Friday from 8:30 am - 5:00 pm PT.
1-800-350-1901 • Fax: 1-626-443-1435 website:
www.miraclesealants.com

Product Damaged During Transportation

If product is damaged during transportation contact Info Trac @ 1-800-535-5053

Warranty

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealants Company shall be to replace such products proven to be defective. **Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein.** Neither seller nor manufacturer shall be liable for any injury or inability to use this product.

Caution

Warning: Detectable amounts of chemicals known to the State of California to cause cancer, birth defects or other reproductive harm may be found in this product. **Tile, Stone & Grout Sealer** may cause irritation of eyes and skin. Avoid contact and prolonged breathing. Use in a well ventilated area. Good ventilation means that fresh air is flowing in such a way as to feel a slight breeze. Open windows and use fans to circulate air. Continue to ventilate until vapors are eliminated. Exposure to high vapor concentration must be avoided. Inhaling the vapors can be harmful. Keep away from heat and open flames. Avoid prolonged contact with skin. Chemical resistant gloves should be worn at all times. Keep small children and pets out of area until product or surfaces has thoroughly dried. **Refer to the SDS for additional information.**

Additional Products

Miracle Sealants Company offers a complete line of water & stain repellents, sealers, cleaner, polishing compounds, diamond abrasives, machinery and accessories for the tile, stone, concrete, metal, fabric and carpet professional or do-it yourself specialist.